

## MATERIAL SAFETY DATA SHEET

MSDS Number: 400792E - 0

24 Hour Emergency Assistance: CHEMTEL (877) 276-7283

General Assistance Number: (877) 276-7285

-----  
SECTION 1 PRODUCT IDENTIFICATION  
-----

MATERIAL IDENTITY: ROTELLA® T Synthetic SAE 5W-40

PRODUCT CODES: 54300

COMPANY ADDRESS: Equilon Enterprises LLC, P. O. Box 4453, Houston, TX.  
77210-4453-----  
SECTION 2 PRODUCT/INGREDIENTS  
-----

CAS#	CONCENTRATION	INGREDIENTS
Mixture	100 %volume	Synthetic Motor Oil
92062-09-4	65 - 74.99 %volume	Hydrotreated Petroleum Slack Wax
64742-54-7	10 - 19.99 %volume	Hydrotreated heavy paraffinic distillate
Mixture	3 - 8.99 %volume	Hydrocracked, hydroisomerized HVI paraffinic oil
Proprietary	3 - 8.99 %volume	Proprietary additives
64742-65-0	1 - 2.99 %volume	Solvent dewaxed heavy paraffinic distillate

-----  
SECTION 3 HAZARDS IDENTIFICATION  
-----

## EMERGENCY OVERVIEW

Appearance &amp; Odor: Dark amber liquid Mild Hydrocarbon Odor

Health Hazards: No known immediate health hazards. May be harmful or fatal if swallowed. Do not induce vomiting. May cause aspiration pneumonitis.

Physical Hazards: No known physical hazards.

NFPA Rating (Health, Fire, Reactivity): 0, 1, 0

Hazard Rating: Least - 0 Slight - 1 Moderate - 2 High - 3

Extreme - 4

Inhalation:

Inhalation of vapors (generated at high temperatures only) or oil mist may cause mild irritation of the nose, throat, and respiratory tract.

**Eye Irritation:**

Lubricating oils are generally considered no more than minimally irritating to the eyes.

**Skin Contact:**

Lubricating oils are generally considered no more than minimally irritating to the skin. Prolonged and repeated contact may result in defatting and drying of the skin that may cause various skin disorders such as dermatitis, folliculitis or oil acne.

**Ingestion:**

This material may be harmful or fatal if swallowed. Ingestion may result in vomiting; aspiration (breathing) of vomitus into lungs must be avoided as even small quantities may result in aspiration pneumonitis.

**Other Health Effects:**

The International Agency for Research on Cancer (IARC) has determined there is sufficient evidence for the carcinogenicity in experimental animals of used gasoline motor oils. Handling procedures and safety precautions in the MSDS should be followed to minimize exposure to the used product.

Material may release hydrogen sulfide (H<sub>2</sub>S), a highly toxic and extremely flammable gas, when heated to 120 Degrees F or higher. H<sub>2</sub>S can cause irritation of the eyes and respiratory tract, headache, dizziness, nausea, vomiting, diarrhea, and pulmonary edema. At concentrations above 300 ppm, respiratory paralysis, causing unconsciousness and death, can occur. The odor ("rotten egg") threshold is 0.02 ppm. Do not depend on sense of smell for warning; H<sub>2</sub>S rapidly deadens the sense of smell.

**Signs and Symptoms:**

Irritation as noted above. Aspiration pneumonitis may be evidenced by coughing, labored breathing and cyanosis (bluish skin); in severe cases death may occur.

**Aggravated Medical Conditions:**

Pre-existing eye, skin and respiratory disorders may be aggravated by exposure to this product.

For additional health information, refer to section 11.

---

SECTION 4 FIRST AID MEASURES

---

**Inhalation:**

Remove victim to fresh air and provide oxygen if breathing is difficult. Get

medical attention.

Skin:

Remove contaminated clothing and shoes and wipe excess from skin. Flush skin with water, then wash with soap and water. If irritation occurs, get medical attention. Do not reuse clothing until cleaned.

Eye:

Flush with water. If irritation occurs, get medical attention.

Ingestion:

Do NOT induce vomiting. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into lungs. Get medical attention.

Note to Physician:

If more than 2.0ml/kg body weight has been ingested and vomiting has not occurred, emesis should be induced with supervision. Keep victim's head below hips to prevent aspiration. If symptoms such as loss of gag reflex, convulsions, or unconsciousness occur before emesis, gastric lavage using a cuffed endotracheal tube should be considered.

---

SECTION 5 FIRE FIGHTING MEASURES

---

Flash Point [Method]: >397 °F/>202.78 °C [ Pensky-Martens Closed Cup]

Extinguishing Media:

Not applicable. Material will float and can be re-ignited on surface of water. Use water fog, 'alcohol foam', dry chemical or carbon dioxide (CO2) to extinguish flames. Do not use a direct stream of water.

Fire Fighting Instructions:

Material will not burn unless preheated. Clear fire area of all non-emergency personnel. Only enter confined fire space with full gear, including a positive pressure, NIOSH-approved, self-contained breathing apparatus. Cool surrounding equipment, fire-exposed containers and structures with water. Container areas exposed to direct flame contact should be cooled with large quantities of water (500 gallons water per minute flame impingement exposure) to prevent weakening of container structure.

---

SECTION 6 ACCIDENTAL RELEASE MEASURES

---

Protective Measures:

May burn although not readily ignitable.

Wear appropriate personal protective equipment when cleaning up spills. Refer to Section 8.

Spill Management:

FOR LARGE SPILLS: Remove with vacuum truck or pump to storage/salvage vessels.

FOR SMALL SPILLS: Soak up residue with an absorbent such as clay, sand or other suitable material. Place in non-leaking container and seal tightly for proper disposal.

Place in container for proper disposal.

Reporting:

CERCLA: Product is covered by EPA's Comprehensive Environmental Response, Compensation and Liability Act (CERCLA) petroleum exclusion. Releases to air, land, or water are not reportable under CERCLA (Superfund).

CWA: This product is an oil as defined under Section 311 of EPA's Clean Water Act (CWA). Spills into or leading to surface waters that cause a sheen must be reported to the National Response Center, 1-800-424-8802.

---

SECTION 7                    HANDLING AND STORAGE

---

Precautionary Measures:

Wash with soap and water before eating, drinking, smoking, applying cosmetics, or using toilet. Launder contaminated clothing before reuse. Properly dispose of contaminated leather articles such as shoes or belts that cannot be decontaminated. Avoid heat, open flames, including pilot lights, and strong oxidizing agents. Use explosion-proof ventilation to prevent vapor accumulation. Ground all handling equipment to prevent sparking.

Material may release hydrogen sulfide (H<sub>2</sub>S), a highly toxic and extremely flammable gas, when heated to 120 Degrees F or higher. H<sub>2</sub>S may collect in the headspace of the container.

Storage:

Store in a cool, dry place with adequate ventilation. Keep away from open flames and high temperatures.

Container Warnings:

Keep containers closed when not in use. Containers, even those that have been emptied, can contain explosive vapors. Do not cut, drill, grind, weld or perform similar operations on or near containers.

---

SECTION 8                    EXPOSURE CONTROLS/PERSONAL PROTECTION

---

Oil mist, mineral	ACGIH TLV	TWA: 5 mg/m3	STEL: 10 mg/m3
Oil mist, mineral	OSHA PEL	TWA: 5 mg/m3	
PARAFFIN WAX FUME	ACGIH TLV	TWA: 2 mg/m3	
PARAFFIN WAX FUME	OSHA PEL - 1989(revoked)	TWA: 2 mg/m3	
Hydrogen sulfide	ACGIH - TLV	TWA: 10 ppm	STEL: 15 ppm
Hydrogen sulfide	OSHA - PEL_IS	TWA: 10 ppm	STEL: 15 ppm
Hydrogen sulfide	Elevated Temperatures	at temperatures >120 Deg F	

#### EXPOSURE CONTROLS

Adequate ventilation to control airborne concentrations below the exposure guidelines/limits.

#### PERSONAL PROTECTION

Personal protective equipment (PPE) selections vary based on potential exposure conditions such as handling practices, concentration and ventilation. Information on the selection of eye, skin and respiratory protection for use with this material is provided below.

##### Eye Protection:

Chemical Goggles - If liquid contact is likely., or Safety glasses with side shields

##### Skin Protection:

Use protective clothing which is chemically resistant to this material. Selection of protective clothing depends on potential exposure conditions and may include gloves, boots, suits and other items. The selection(s) should take into account such factors as job task, type of exposure and durability requirements.

Published literature, test data and/or glove and clothing manufacturers indicate the best protection is provided by:

Neoprene, or Nitrile Rubber

##### Respiratory Protection:

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, an approved respirator must be worn. Respirator selection, use and maintenance should be in accordance with the requirements of the OSHA Respiratory Protection Standard, 29 CFR 1910.134.

Types of respirator(s) to be considered in the selection process include:

For Mist: Air Purifying, R or P style NIOSH approved respirator. For Vapors: Air Purifying, R or P style prefilter & organic cartridge, NIOSH approved respirator. Self-contained breathing apparatus.

---

**SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES**

---

Appearance & Odor: Dark amber liquid Mild Hydrocarbon Odor

Substance Chemical Family: Lubricants

Appearance: Dark amber liquid

Flash Point: > 397 °F [Pensky-Martens Closed Cup]

Pour Point: -27 °F

Specific Gravity: 0.888

Viscosity: 14 cSt - 15 cSt @ 40 °C

---

**SECTION 10 REACTIVITY AND STABILITY**

---

Stability:

Material is stable under normal conditions.

Conditions to Avoid:

Avoid heat and open flames.

Materials to Avoid:

Avoid contact with strong oxidizing agents.

Hazardous Decomposition Products:

Thermal decomposition products are highly dependent on combustion conditions. A complex mixture of airborne solids, liquids and gases will evolve when this material undergoes pyrolysis or combustion. Aldehydes, Carbon Monoxide, Carbon Dioxide, Hydrogen Sulfide, Ketones and other unidentified organic compounds may be formed upon combustion.

---

**SECTION 11 TOXICOLOGICAL INFORMATION**

---

Acute Toxicity

Dermal LD50 >5.0 g/kg(Rabbit) OSHA: Non-Toxic Based on components(s)

Oral LD50 >5.0 g/kg(Rat) OSHA: Non-Toxic Based on components(s)

Carcinogenicity Classification

Synthetic Motor Oil

NTP: No IARC: Not Reviewed by IARC ACGIH: Not Reviewed OSHA: No

---

SECTION 12            ECOLOGICAL INFORMATION

---

Environmental Impact Summary:

There is no ecological data available for this product. However, this product is an oil. It is persistent and does not readily biodegrade. However, it does not bioaccumulate.

---

SECTION 13            DISPOSAL CONSIDERATIONS

---

RCRA Information:

Under RCRA, it is the responsibility of the user of the material to determine, at the time of the disposal, whether the material meets RCRA criteria for hazardous waste. This is because material uses, transformations, mixtures, processes, etc. may affect the classification. Refer to the latest EPA, state and local regulations regarding proper disposal.

---

SECTION 14            TRANSPORT INFORMATION

---

US Department of Transportation Classification

This material is not subject to DOT regulations under 49 CFR Parts 171-180.

Oil: This product is an oil under 49CFR (DOT) Part 130. If shipped by rail or highway in a tank with a capacity of 3500 gallons or more, it is subject to these requirements. Mixtures or solutions containing 10% or more of this product may also be subject to this rule.

International Air Transport Association

Not regulated under IATA rules.

International Maritime Organization Classification

Not regulated under International Maritime Organization rules.

---

SECTION 15            REGULATORY INFORMATION

---

FEDERAL REGULATORY STATUS

OSHA Classification:

Product is hazardous according to the OSHA Hazard Communication Standard, 29 CFR 19.10.1200, because it carries the occupational exposure limit for mineral oil mist.

Ozone Depleting Substances (40 CFR 82 Clean Air Act):

This material does not contain nor was it directly manufactured with any Class I or Class II ozone depleting substances.

Superfund Amendment & Reauthorization Act (SARA) Title III:

There are no components in this product on the SARA 302 list.

SARA Hazard Categories (311/312):

Immediate Health:NO Delayed Health:NO Fire:NO Pressure:NO  
Reactivity:NO

SARA Toxic Release Inventory (TRI) (313):

There are no components in this product on the SARA 313 list.

Toxic Substances Control Act (TSCA) Status:

All component(s) of this material is(are) listed on the EPA/TSCA Inventory of Chemical Substances.

Other Chemical Inventories:

Component(s) of this material is (are) listed on the Canadian DSL

State Regulation

The following chemicals are specifically listed by individual states; other product specific health and safety data in other sections of the MSDS may also be applicable for state requirements. For details on your regulatory requirements you should contact the appropriate agency in your state.

Pennsylvania Right-To-Know Chemical List:

PARAFFIN WAXES AND HYDROCARBON WAXES 65 - 74.99 %volume Environmental Hazard

-----  
SECTION 16 OTHER INFORMATION  
-----

HMIS Rating (Health, Fire, Reactivity): 0, 1, 0

Revision#: 0

Revision Date: 10/19/2001

Revisions since last change (discussion): This Material Safety Data Sheet (MSDS) has been newly created to fully comply with the guidance contained in the ANSI MSDS standard (ANSI Z400.1-1998). We encourage you to take the

opportunity to read the MSDS and review the information contained therein.

-----  
SECTION 17 LABEL INFORMATION  
-----

READ AND UNDERSTAND MATERIAL SAFETY DATA SHEET BEFORE HANDLING OR DISPOSING OF PRODUCT. THIS LABEL COMPLIES WITH THE REQUIREMENTS OF THE OSHA HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200) FOR USE IN THE WORKPLACE. THIS LABEL IS NOT INTENDED TO BE USED WITH PACKAGING INTENDED FOR SALE TO CONSUMERS AND MAY NOT CONFORM WITH THE REQUIREMENTS OF THE CONSUMER PRODUCT SAFETY ACT OR OTHER RELATED REGULATORY REQUIREMENTS.

PRODUCT CODES: 54300

ROTELLA® T Synthetic SAE 5W-40

CAUTION!

ASPIRATION HAZARD IF SWALLOWED - CAN ENTER LUNGS AND CAUSE DAMAGE. PROLONGED OR REPEATED SKIN CONTACT MAY CAUSE OIL ACNE OR DERMATITIS. USED GASOLINE ENGINE OIL HAS BEEN SHOWN TO CAUSE CANCER IN LABORATORY ANIMALS.

Precautionary Measures:

Avoid prolonged or repeated contact with eyes, skin and clothing. Do not take internally. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling.

FIRST AID

Inhalation: Remove victim to fresh air and provide oxygen if breathing is difficult. Get medical attention.

Skin Contact: Remove contaminated clothing and shoes and wipe excess from skin. Flush skin with water, then wash with soap and water. If irritation occurs, get medical attention. Do not reuse clothing until cleaned.

Eye Contact: Flush with water. If irritation occurs, get medical attention.

Ingestion: Do NOT induce vomiting. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into lungs. Get medical attention.

FIRE

In case of fire, Use water fog, 'alcohol foam', dry chemical or carbon dioxide (CO2) to extinguish flames. Do not use a direct stream of water. Not applicable. Material will float and can be re-ignited on surface of water.

SPILL OR LEAK

Dike and contain spill.

FOR LARGE SPILLS: Remove with vacuum truck or pump to storage/salvage vessels.

FOR SMALL SPILLS: Soak up residue with an absorbent such as clay, sand or other suitable material. Place in non-leaking container and seal tightly for proper disposal.

CONTAINS: Hydrotreated Petroleum Slack Wax, 92062-09-4; Hydrotreated heavy paraffinic distillate, 64742-54-7; Hydrocracked, hydroisomerized HVI paraffinic oil, Mixture; Proprietary additives, Proprietary; Solvent dewaxed heavy paraffinic distillate, 64742-65-0

NFPA Rating (Health, Fire, Reactivity): 0, 1, 0

HMIS Rating (Health, Fire, Reactivity): 0, 1, 0

#### TRANSPORTATION

US Department of Transportation Classification

This material is not subject to DOT regulations under 49 CFR Parts 171-180.

Oil: This product is an oil under 49CFR (DOT) Part 130. If shipped by rail or highway in a tank with a capacity of 3500 gallons or more, it is subject to these requirements. Mixtures or solutions containing 10% or more of this product may also be subject to this rule.

CAUTION: Misuse of empty containers can be hazardous. Empty containers can be hazardous if used to store toxic, flammable, or reactive materials. Cutting or welding of empty containers might cause fire, explosion or toxic fumes from residues. Do not pressurize or expose to open flames or heat. Keep container closed and drum bungs in place.

#### Name and Address

Equilon Enterprises LLC  
P. O. Box 4453  
Houston, TX 77210-4453

TRANSPORTATION EMERGENCY                      CHEMTEL    (877) 276-7283

HEALTH EMERGENCY                                      CHEMTEL    (877) 276-7283

#### ADMINISTRATIVE INFORMATION

COMPANY ADDRESS:        Equilon Enterprises LLC, P. O. Box 4453, Houston, TX.  
77210-4453

Company Product Stewardship & Regulatory Compliance Contact: Timothy W Childs  
Phone Number:        (281) 874-7708

MSDS FAX-BACK Phone Number: (877) 276-7285

THE INFORMATION CONTAINED IN THIS DATA SHEET IS BASED ON THE DATA AVAILABLE TO US AT THIS TIME, AND IS BELIEVED TO BE ACCURATE BASED UPON THAT DATA. IT IS PROVIDED INDEPENDENTLY OF ANY SALE OF THE PRODUCT, FOR PURPOSE OF HAZARD COMMUNICATION. IT IS NOT INTENDED TO CONSTITUTE PRODUCT PERFORMANCE INFORMATION, AND NO EXPRESS OR IMPLIED WARRANTY OF ANY KIND IS MADE WITH RESPECT TO THE PRODUCT, UNDERLYING DATA OR THE INFORMATION CONTAINED HEREIN. YOU ARE URGED TO OBTAIN DATA SHEETS FOR ALL PRODUCTS YOU BUY, PROCESS, USE OR DISTRIBUTE, AND ARE ENCOURAGED TO ADVISE THOSE WHO MAY COME IN CONTACT WITH SUCH PRODUCTS OF THE INFORMATION CONTAINED HEREIN.

TO DETERMINE THE APPLICABILITY OR EFFECT OF ANY LAW OR REGULATION WITH RESPECT TO THE PRODUCT, YOU SHOULD CONSULT WITH YOUR LEGAL ADVISOR OR THE APPROPRIATE GOVERNMENT AGENCY. WE WILL NOT PROVIDE ADVICE ON SUCH MATTERS, OR BE RESPONSIBLE FOR ANY INJURY FROM THE USE OF THE PRODUCT DESCRIBED HEREIN. THE UNDERLYING DATA, AND THE INFORMATION PROVIDED HEREIN AS A RESULT OF THAT DATA, IS THE PROPERTY OF EQUIVA SERVICES LLC AND IS NOT TO BE THE SUBJECT OF SALE OR EXCHANGE WITHOUT THE EXPRESS WRITTEN CONSENT OF EQUIVA SERVICES LLC.

35138-11855-100R-10/19/2001