

Material Safety Data Sheet

Section 1 A401

Manufacturer's Name
CERTIFIED PRODUCTS, INC.
Address
1075 NORTH CR 427
City, State, Zip Code
LONGWOOD, FL 32750

Product Name
SUPERSLICK SLICK STUFF
Emergency Phone No.
407-830-7775
EPA REGISTRATION NUMBER

EPA ESTABLISHED NUMBER

Section 2 - Ingredients

	%	TVL
PROPRIETARY BLEND OF BASE OILS INHIBITORS , SOLVENTS AND ADDITIVES		65
HYDROCARBON PROPELLANT-PROPANE/ISOBUTANE		35

Section 3 - Physical Data

Boiling Point (F) : N/A

Specific Gravity : N/A

Appearance and Odor : MILD SWEET SOLVENT ODOR.

Solubility Water : N/A

Solubility Oil : N/A

Section 4 - Fire Hazard Data

Flash Point: (Method) : N/A

Extinguishing Media : FOAM, CARBON DIOXIDE, DRY CHEMICAL. WATER IS UNSUITABLE ON BURNING LIQUID (EXCEPT TO COOL CONTAINERS).

Special Procedures : CONCENTRATED VAPORS CAN BE IGNITED BY HIGH INTENSITY IGNITION SOURCE. FIRE FIGHTER SHOULD WEAR SELF CONTAINED POSITIVE PRESSURE BREATHING APPARATUS. EXCESSIVE HEAT MAY CAUSE AEROSOL TO BURST.

Unusual Fire and Explosion Hazards : HAZARDOUS DECOMPOSITION PRODUCTS MAY FORM TOXIC MATERIAL, CARBON DIOXIDE AND CARBON MONOXIDE, VARIOUS HYDROCARBONS.

Section 5 - Health Hazard Data

Toxicity Category :

N/A

Oral LD50:

N/A

Dermal LD50:

N/A

Inhalation LC50:

N/A

Effects of Overexposure

Eyes : CAN CAUSE SEVERE IRRITATION, REDNESS, TEARING AND BLURRED VISION.

Skin: PROLONGED OR REPEATED CONTACT CAN CAUSE MODERATE IRRITATION, DEFATTING, DERMATITIS.

Inhalation:

Ingestion:

Emergency First Aid Procedures

Eyes: FLUSH WITH LARGE AMOUNTS OF WATER, LIFTING UPPER AND LOWER LIDS OCCASIONALLY, GET MEDICAL ATTENTION.

Skin: THOROUGHLY WASH EXPOSED AREA WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING. LAUNDRY CONTAMINATED CLOTHING BEFORE RE USE.

Inhalation: IF AFFECTED, REMOVE INDIVIDUAL TO FRESH AIR. IF BREATHING IS DIFFICULT, ADMINISTER OXYGEN. IF BREATHING HAS STOPPED GIVE ARTIFICIAL RESPIRATION KEEP PERSON WARM, QUIET AND GET MEDICAL ATTENTION. DO NOT GIVE STIMULANTS.

Ingestion: DO NOT INDUCE VOMITING. IMMEDIATELY DRINK TWO GLASSES OF WATER. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. CALL A PHYSICIAN OR TRANSPORT TO EMERGENCY FACILITY.

Section 6 - Reactivity Data

Stability:

Incompatibility: STRONG OXIDIZING AGENTS. ACIDIC AGENTS, INCLUDING CLAYS.

Hazardous Decomposition: CARBON MONOXIDE IS A PRODUCT FROM INCOMPLETE COMBUSTION.

Hazardous Polymerization:

Section 7 - Spill or Leak Procedure

Procedure In Case of Release or Spill: EVACUATE THE AREA, VENTILATE AND AVOID BREATHING VAPORS. CONTAIN THE SPILL. REMOVE LEAKING CONTAINER AND TRANSFER PRODUCT TO ANOTHER VESSEL. CLEAN UP AREA BY MOPPING OR SOAKING UP WITH ABSORBENT MATERIAL. PLACE IN CLOSED CONTAINERS. DO NOT FLUSH TO SEWER. (DO NOT USE CLAY)

Waste Disposal Method: RECOVERED MATERIAL MAY BE SENT TO LICENSED RECLAIMER OR INCINERATOR. CONSULT LOCAL, STATE AND FEDERAL DISPOSAL AUTHORITIES FOR APPROVED PROCEDURES.

Section 8 - Special Protection Information

Respiratory Protection: NONE REQUIRED IF GOOD VENTILATION IS MAINTAINED. IF VAPOR CONCENTRATION RISES ABOVE TLV, USE NIOSH APPROVED ORGANIC VAPOR CARTRIDGE FOR LARGE SPILLS OR EMERGENCIES IN COMPLETELY ENCLOSED AREA, USE SELF CONTAINED BREATHING APPARATUS.

Ventilation : USE IN WELL VENTILATED AREA.

Protection Gloves: USE SOLVENT RESISTANT GLOVES FOR LIQUID HANDLING.

Eye Protection: FOR SPRAYING OR SPLASHING OF SOLVENT USE FACE SHIELD OR GOGGLES.

Precautions in Handling and Storage: STORE AEROSOL BELOW 120°F AND ABOVE 32°F. STORE ALL MATERIALS IN DRY, WELL VENTILATED AREA. AVOID BREATHING VAPORS. WASH HANDS WITH SOAP AND WATER AFTER USE AND/OR BEFORE BREAKS, LUNCH AND AT THE END OF WORK PERIODS. REMOVE CONTAMINATED CLOTHING AND LAUNDRY BEFORE REUSE.