



Wynn's Canada Ltd. 7090 Edwards Blvd. Mississauga, Ontario Canada L5S 1Z1
(905) 670-3881 Fax: (905) 670-3829

MATERIAL SAFETY DATA SHEET

SECTION 01 : MATERIAL NAME/IDENTIFIER

PRODUCT NAME XTEND POWER STEERING FLUID (PART #51929)
MANUFACTURER..... WYNN'S CANADA LTD.
 7090 EDWARDS BLVD.
 MISSISSAUGA, ONTARIO L5S 1Z1
 CHEMTREC 24 HOUR EMERGENCY TELEPHONE # (703) 527-3887 CALL COLLECT

CHEMICAL NAME NA
CHEMICAL FAMILY NA
CHEMICAL FORMULA..... 51929
TRADE NAME AND SYNONYMS POWER STEERING FLUID
MOLECULAR WEIGHT NA
MATERIAL USE..... NA

SECTION 02: HAZARDOUS INGREDIENTS

HAZARDOUS INGREDIENTS	APPROXIMATE CONDENSATION %	C.A.S., N.A. OR U.N. NUMBERS	LD/50, ROUTE, SPECIES	LC/50, ROUTE, SPECIES
NONE INDICATED	NA	NA	NA	NA

SECTION 03: PHYSICAL DATA

PHYSICAL STATE.....LIQUID
ODOUR THRESHOLD (P.P.M)NA
SPECIFIC GRAVITY.....0.85
VAPOUR PRESSURENA
VAPOUR DENSITY (AIR=1).....NA
EVAPORATION RATENA
BOILING POINT (°C).....NA
FREEZING POINT (°C)NA
SOLUBILITY IN WATER (20°C).....NONE
% VOLATILE (BY VOLUME)NA
pH.....NA
COEFFICIENT OF WATER/OIL DISTRIBUTION.....NA

PRODUCT NAME XTEND POWER STEERING FLUID

SECTION 04: FIRE AND EXPLOSION DATA

FLAMMABILITY NA

IF YES, UNDER WHICH CONDITIONS?.....

MEANS OF EXTINCTION DRY CHEMICALS, CO₂, FOAM, WATER FOG.

SPECIAL PROCEDURES STANDARD PETROLEUM PROCEDURES.

FLASHPOINT (°C) AND METHOD ASTM D-92 215°C

UPPER EXPLOSION LIMIT (% BY VOLUME) NA

LOWER EXPLOSION LIMIT (% BY VOLUME) NA

AUTOIGNITION TEMPERATURE (°C) NA

HAZARDOUS COMBUSTION PRODUCTS NA

EXPLOSION DATA

SENSITIVITY TO MECHANICAL IMPACT NA

SENSITIVITY TO STATIC DISCHARGE NA

SECTION 05: REACTIVITY DATA

CHEMICAL STABILITY YES

IF NO, UNDER WHICH CONDITIONS?.....

INCOMPATIBILITY TO OTHER SUBSTANCES YES

IF SO, WHICH ONES? WATER, STRONG OXIDIZERS.

REACTIVITY AND UNDER WHAT CONDITIONS? NA

HAZARDOUS DECOMPOSITION PRODUCTS MAY PRODUCE OXIDES OF CARBON, SULFUR, PHOSPHOROUS, ZINC.

SECTION 06: TOXICOLOGICAL PROPERTIES

ROUTE OF ENTRY:

SKIN CONTACT

SKIN ABSORPTION.....

EYE CONTACT

INHALATION

INHALATION CHRONIC

INGESTION

PRODUCT NAME XTEND POWER STEERING FLUID

EFFECTS OF ACUTE EXPOSURE : MAY BE IRRITANT TO EYES.

EFFECTS OF CHRONIC EXPOSURE : NA

EXPOSURE LIMITS NA

IRRITANCY OF MATERIAL..... NA

SENSITIZATION OF MATERIAL..... NA

SYNERGISTIC MATERIALS NA

CARCINOGENICITY, REPRODUCTIVE EFFECTS,
TERATOGENICITY, MUTAGENICITY NA

SECTION 07: PREVENTIVE MEASURES

PERSONAL PROTECTIVE EQUIPMENT

GLOVES (SPECIFY) PLASTIC, NEOPRENE

EYE (SPECIFY) SAFETY GLASSES

RESPIRATORY (SPECIFY) NONE NORMALLY REQUIRED.

OTHER (SPECIFY)..... NA

ENGINEERING CONTROLS..... NONE

LEAK AND SPILL PROCEDURE USE ABSORBENT SAND OR CLAY.

WASTE DISPOSAL OBSERVE LOCAL, PROVINCIAL, FEDERAL REGULATIONS.

HANDLING PROCEDURES AND EQUIPMENT HANDLE WITH REASONABLE CARE.

STORAGE REQUIREMENTS STORE IN COOL DRY PLACE.

SPECIAL SHIPPING INFORMATION NA

PRODUCT NAME XTEND POWER STEERING FLUID

SECTION 08: FIRST AID MEASURES

SKIN: WASH WITH SOAP AND WATER.

EYES: FLUSH WITH LARGE VOLUMES OF WATER.

ADDITIONAL INFORMATION

SECTION 09: PREPARATION DATE OF M.S.D.S

PREPARED BY..... TECHNICAL DEPARTMENT

TELEPHONE NUMBER.....(905) 670-3881

DATE 11/22/2002

ADDITIONAL NOTES OR REFERENCES: